




Electric Stacker - ZDYC Series Electric Stacker



Introduce:

The product has passed the CE certification and is mainly applied in petroleum, chemical engineering, pharmacy, light textile, military engineering, painting, coal, port, railroad, warehouse, bridge back, etc. for load and unload, pile and move.

- 1)It adopts double mast and chain driving technology.
- 2)The controlling system is programmable based on the imported advanced foreign technology.
- 3)Moving type: electric driving and climbing to a certain gradient.
- 4)The rising height and load can be changed as required by the customers.
- 5)There are complete safety equipments and their technical performance has reached the advanced level as the international product.



Parameters:

| Model No. | | ZDYC10-25 | ZDYC10-30 | ZDYC10-35 |
|-------------------------|------|------------------|------------------|------------------|
| Rated Capacity | kg | 1000 | | |
| Load Center | mm | 500 | | |
| Max. Fork Height | | 2500 | 3000 | 3500 |
| Max. Machine Height | | 2975 | 3475 | 3975 |
| Handle Height | | 1385-1405 | | |
| Fork Size | | 1125*160 | | |
| Fork Width | | 570 | | |
| Min. Turning Radius | | 1700 | | |
| Wheel Base | | 1348 | | |
| Front-Wheel Distance | | 370 | | |
| Max. Speed Without Load | | km/h | 4.5-5 | |
| Max. Speed With Load | km/h | 3.8-4.2 | | |
| Max. Travel Grade | % | 8-10 | | |
| Driving Motor | v/kw | 24/1.2 | | |
| Lifting Motor | v/kw | 24/2-3 | | |
| Battery | v/Ah | 24/240-270 | | |
| Charger | v/A | 24/30-40 | | |
| Overall Length | mm | 2040 | | |
| Overall Width | | 856 | | |
| Overall Height | | 1770 | 2020 | 2270 |
| Overall Net Weight | kg | 858 | 880 | 900 |

| Model No. | | ZDYC15-25 | ZDYC15-30 | ZDYC15-35 | ZDYC20-25 |
|-------------------------|------|------------------|------------------|------------------|------------------|
| Rated Capacity | kg | 1500 | | | 2000 |
| Load Center | mm | 400 | | | |
| Max. Fork Height | | 2500 | 3000 | 3500 | 2500 |
| Max. Machine Height | | 2975 | 3475 | 3975 | 3095 |
| Handle Height | | 1385-1405 | | | |
| Fork Size | | 1125*160 | | | 1125*180 |
| Fork Width | | 570 | | | 590 |
| Min. Turning Radius | | 1750 | | | |
| Wheel Base | | 1398 | | | |
| Front-Wheel Distance | | 320 | | | |
| Max. Speed Without Load | | km/h | 5-6 | | |
| Max. Speed With Load | km/h | 4-5 | | | |
| Max. Travel Grade | % | 8-10 | | | |
| Driving Motor | v/kw | 24/1.2-1.3 | | | |
| Lifting Motor | v/kw | 24/2-3 | | | |
| Battery | v/Ah | 24/240-270 | | | |
| Charger | v/A | 24/30-40 | | | |
| Overall Length | mm | 2040 | | | |
| Overall Width | | 856 | | | |
| Overall Height | | 1770 | 2020 | 2270 | 1890 |
| Overall Net Weight | kg | 888 | 910 | 930 | 988 |

| Model No. | | ZDYC10-40 | ZDYC10-45 | ZDYC10-50 |
|-------------------------|------|------------|-----------|-----------|
| Rated Capacity | kg | 1000 | | |
| Load Center | | 400 | | |
| Max. Fork Height | | 4000 | 4500 | 5000 |
| Max. Machine Height | | 4540 | 5040 | 5540 |
| Handle Height | | 1385-1405 | | |
| Fork Size | mm | 1125*160 | | |
| Fork Width | | 685 | | |
| Min. Turning Radius | | 1750 | | |
| Wheel Base | | 1398 | | |
| Front-Wheel Distance | | 337 | | |
| Max. Speed Without Load | km/h | 5-6 | | |
| Max. Speed With Load | | 4-5 | | |
| Max. Travel Grade | % | 8-10 | | |
| Driving Motor | v/kw | 24/1.2-1.3 | | |
| Lifting Motor | | 24/2-3 | | |
| Battery | v/Ah | 24/240-270 | | |
| Charger | v/A | 24/30-40 | | |
| Overall Length | | 2060 | | |
| Overall Width | mm | 856 | | |
| Overall Height | | 1935 | 2100 | 2265 |
| Overall Net Weight | kg | 1000 | 1025 | 1050 |



סי.איי.אל חברה להנדסה בע"מ

מפיצים יבואנים בישראל

טלפון: 08-9330799 , פקס: 08-9330804

www.cil1.com

